



BREMSKERL



BREMSKERL 7000

Disc brake pad for rail vehicles up to 220km/h

Standard disc brake pad for medium to high loads

UIC - Passenger coaches

Material: Organic composite formulation
Contains metal | Asbestos free | Heavy metal free

Characteristics: Reduced smell | Excellent wet performance | UIC approved
Fire protection certificate acc. EN 45545-2 (R22/R23; HL1, HL2, HL3)



BREMSKERL

BK

7000

CAPACITY

max. specific pressure	105 N/cm ²
max. sliding speed	60 m/s
max. continuous application temperature	370 °C
max. short time application temperature	460 °C




TECHNICAL DATA

Average coefficient of friction (dry)	0.37	
Average pad wear	0.17 cm ³ /MJ	
Hardness	42 N/mm ²	DIN EN ISO 2039-1
Tensile Strength	3.8 MPa	DIN EN ISO 527
Impact Strength	4.3 kJ/m ²	DIN EN ISO 179-1
Density	2.0 g/cm ³	DIN EN ISO 1183

FRICTION CHARACTERISTICS

Test programme: Tab C.3; Nr. S1 class 4.2 acc. UIC 541-3



07/2026

BREMSKERL-REIBBELAGWERKE
EMMERLING GMBH & CO. KG
Brakenhof 7 • 31629 Estorf • Germany

+ 49 (0) 5025 978-0
info@bremskerl.com
www.bremskerl.com

