



BREMSKERL

BK

2100



BREMSKERL 2100

Disc brake pad for rail vehicles up to 220km/h

Next generation disc brake pad for medium to high loads

Material: Organic composite formulation
Contains metal | Asbestos free | Heavy metal free

Characteristics: Low wear rates | Excellent wet performance
UIC approved



BREMSKERL

BK

2100

CAPACITY

max. specific pressure	85 N/cm ²
max. sliding speed	55 m/s
max. continuous application temperature	360 °C
max. short time application temperature	450 °C




TECHNICAL DATA

Average coefficient of friction (dry)	0.35	
Average pad wear	0.19 cm ³ /MJ	
Hardness	38 N/mm ²	DIN EN ISO 2039-1
Tensile Strength	4.6 MPa	DIN EN ISO 527
Impact Strength	5.2 kJ/m ²	DIN EN ISO 179-1
Density	2.06 g/cm ³	DIN EN ISO 1183

FRICTION CHARACTERISTICS

Test programme: Tab C.3; Nr. S1 class 4.2 acc. UIC 541-3



07/2026

BREMSKERL-REIBBELAGWERKE
EMMERLING GMBH & CO. KG
Brakenhof 7 • 31629 Estorf • Germany

+ 49 (0) 5025 978-0
info@bremskerl.com
www.bremskerl.com

